

Specifications

Eaton EMAT08-10



Eaton Managed PDU, 1PH, 1U, NEMA 5-15P input, 10 ft cord, 1.44kW, 12A, 120V, 8 Outlets (8) 5-15R



General specifications

PRODUCT NAME	Eaton managed PDU
CATALOG NUMBER	EMAT08-10
UPC	743172082657
PRODUCT LENGTH/DEPTH	19 in
PRODUCT HEIGHT	8 in
PRODUCT WIDTH	1.69 in
PRODUCT WEIGHT	6.9 lb
WARRANTY	3 year
COMPLIANCES	Contact Manufacturer
CERTIFICATIONS	UL Listed

Product specifications

FORM FACTOR	1U
OUTLET CONTROL	Yes
PHASE	Single-phase
WATTAGE	1.44 kW max
AMPERAGE RATING	12A
INPUT VOLTAGE	120V
INPUT CONNECTION	5-15P
OUTLETS	(8) 5-15R
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS

[Eaton ePDU certificate of volatility](#)

[Eaton RoHS Declaration of Conformity: ePDU G3](#)

DRAWINGS

[Eaton Advanced Monitored and Managed ePDU visio stencil](#)

[Eaton ePDU Managed EMAT08-10 technical drawing](#)

[Eaton ePDU G3 instruction set - system objects](#)

[Eaton ePDU G3 operations manual](#)

[Eaton ePDU G3 replace and configure eNMC module](#)

[Eaton Double-wide G3 ePDU installation and connectivity quick start guide](#)

[Eaton ePDU G3 1U and 2U installation addendum](#)

MANUALS AND USER GUIDES

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - EMAT08-10](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

